
JZTC2 F & M Angle-type Needle Valve / Stainless Steel Metering Flow Control NeedleValves/
Stainless steel Flow Control Instrumentation 316 Forged Angle Male Female Needle Valve /









-JZTC2 F & M Angle-type Needle Valve

Order information	End Connection	Orifice		Flow coefficient	A		B		H		F	
		(in)	(mm)	Cv	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)
-JZTC2-FM-2	NPT1/8	0.080	2.0	0.09	1.36	34.5	1.02	26.0	1.66	42.2	1.75	44.4
-JZTC2-FM-4	NPT1/4	0.125	3.2	0.21	1.36	34.5	1.02	26.0	1.66	42.2	1.75	44.4
-JZTC2-FM- 6	NPT3/8	0.250	6.4	0.73	1.61	41.0	1.24	31.5	2.31	58.7	2.50	63.5
-JZTC2-FM- 8	NPT1/2	0.250	6.4	0.73	1.72	43.8	1.56	39.5	2.31	58.7	2.50	63.5
-JZTC2-FM- R2	BSPT1/8	0.080	2.0	0.09	1.36	34.5	1.02	26.0	1.66	42.2	1.75	44.4
-JZTC2-FM- R4	BSPT1/4	0.125	3.2	0.21	1.36	34.5	1.02	26.0	1.66	42.2	1.75	44.4
-JZTC2-FM- R6	BSPT3/8	0.250	6.4	0.73	1.61	41.0	1.24	31.5	2.31	58.7	2.50	63.5
-JZTC2-FM- R8	BSPT1/2	0.250	6.4	0.73	1.72	43.8	1.56	39.5	2.31	58.7	2.50	63.5

All dimensions are in millimeters unless otherwise specified and only for reference subject to change.

www.sklok.com
EMAIL:sales@sklok.com